

Vigilant®



- **Industrial Applications**
- UL 1598/A, CSA, NOM, CE, UKCA, RCM
- 11,000-41,300 lumens
- Up to 200 lm/W
- 100-277 VAC, 120-250 VDC, 347/480 VAC
- Up to 60' (18m) mounting height
- 10 year warranty

Ratings: IP66/67, NEMA 4X, IK05/IK06/IK10

Operating Voltage: 100-277 VAC, 120-250 VDC and 347-480 VAC

Lumen Type: 11.000 – 41.300 lumens

Operating temperature range of: -40°F to +149°F (-40°C to +65°C)

SafeSite®



- **Hazardous Location**
- UL 844 (CID1, CID2, CII, CIII), CSA, IECEx/ATEX (Zone 1)
- 11,000-41,300 lumens
- Up to 200 lm/W
- 100-277 VAC, 120-250 VDC, 347-480 VAC
- Up to 60' (18m) mounting height
- 10 year warranty

Ratings: IP66/67, NEMA 4X, IK05/IK06/IK10

Operating Voltage: 100-277 VAC, 120-250 VDC and 347-480 VAC

Lumen Type: 9,500 - 41,300 lumens

Operating temperature range of: --40°F to +149°F (-40°C to +65°C)

Reliant™ - AMERICAS



- **Non-Hazardous**
- UL 1598, CSA
- 18,000-72,000 lumens
- Up to 160 lm/W
- 100-277 VAC, 347-480 VAC
- Up to 100' mounting height (tandem models)
- 10 year warranty

Ratings: Damp Location

Operating Voltage: 100-277 VAC, 347-480 VAC; 6kV surge upgradeable to 10kV

Lumen Type: 18,000 to 72,000 lumens

Operating temperature range of: --40°F to +131°F (standard model)

Reliant™ - EMEA/APAC



- **Non-Hazardous**
- CE, ENEC, RCM
- 11,000-36,000 lumens
- Up to 160 lm/W
- 100-277 VAC
- Up to 40' (12m) mounting height
- 10 year warranty

Ratings: IP66

Operating Voltage: 100-277 VAC

Lumen Type: 11,000 to 36,000 lumens

Operating temperature range of: -40°C to +55°C

Vigilant® - Low Profile



- **Non-Hazardous**
- UL 1598/A, CE, CSA
- 42,900 – 70,500 lumens
- Up to 155 lm/W
- 120-277 VAC, 208 VAC, 347 VAC, 480 VAC
- Up to 100' (30m) Mounting Height
- 10 year warranty
- DLC Premium on most models
- Only 7" tall and 48lbs

Ratings: IP66/67, DLC Premium (most models)

Operating Voltage: 120-277 VAC, 208 VAC, 347 VAC, 480 VAC

Lumen Type: 42,900 - 70,500 Lumens

Operating temperature range of: -40°F to +149°F (-40°C to +65°C)

Vigilant®



- **Non-Hazardous**
- UL 1598/A, CE, CSA, ENEC, RCM
- 42,500-72,000 lumens
- Up to 149 lm/W
- 120-277 VAC, 347 VAC, 415 VAC, 480 VAC
- Up to 100' (30m) Mounting Height
- 10 year warranty

Ratings: IP66/67

Operating Voltage: 120-277 VAC, 347 VAC, 415 VAC, 480 VAC

Lumen Type: 42,500 - 72,000 lumens

Operating temperature range of: -40°F to +149°F (-40°C to +65°C)

Vigilant®



- **Industrial Applications**

- UL 1598/a, CSA, NOM, CE, UKCA, RCM
 - 4,000 – 16,500 lumens
 - Up to 148 lm/W
 - 100-277 VAC, 120-250 VDC, 347/480 VAC
 - Up to 20' (6m) Mounting Height
 - 10 year warranty
-

Ratings: IP66/67, NEMA 4X, IK05/IK06/IK10

Operating Voltage: 100-277 VAC, 120-250 VDC and 347-480 VAC

Lumen Type: 4,400 - 17,200 lumens

Operating temperature range of: 40°F to +149°F (-40°C to +65°C)

SafeSite®



- **Hazardous Location**

- UL 844 (CID2, CII, CIII), CSA
 - 4,000 – 16,800 lumens
 - Up to 148 lm/W
 - 100-277 VAC, 120-250 VDC, 347/480 VAC
 - Up to 20' (6m) Mounting Height
 - 10 year warranty
-

Ratings: IP66/67, NEMA 4X, IK05/IK06/IK10

Operating Voltage: 100-277 VAC, 120-250 VDC and 347-480 VAC

Lumen Type: 4,400 - 17,200 lumens

Operating temperature range of: -40°F to +149°F (-40°C to +65°C)